

## Uniview switch IPC6854SR-X38UP-VC

Šifra: 526  
Kategorija proizvoda: IP KAMERE  
Proizvođač: UNIVIEW



Cena: **rsd 280.800,00**

**IPC6854SR-X38UP-VC****4 MP Speed Dome AI Metadata PTZ kamera sa 38x optičkim zoom-om**

- Rezolucija snimanja:** 2688\*1520 resolution,60fps
- Čip:** 1/1.8", 4.0 megapixel, progressive scan, CMOS
- Šater:** Auto/Manual, 1 ~ 1/100000s
- Optika:** 5.7 ~ 216.6mm, automatski fokus
- Osetljivost:** Color: 0.0005Lux (F1.3, AGC ON)0Lux with IR on, 120db WDR
- IC domet:** do 250m
- PTZ komande:** 16 patrola i 1024 preseta po patroli, Home pozicija.
- Interfejsi:** 10/100M Base-TX Ethernet, Micro SD do 256GB, 2x Alarmna ulaza, 1 Alarmni izlaz, RS485
- Protokoli:** IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS.
- Mrežni standardi:** ONVIF (Profile S, Profile T), API
- Kompresija:** Ultra 265, H.265, H.264, MJPEG
- Smart funkcije:** Intrusion Detection, Cross line, Object left behind and object removed detection, Motion detection, Tampering alarm, Audio Detection, Defocus Detection, People counting, Face detection.
- Ostale Karakteristike:** Optičkil Defog i Digitalni Defog, 2D/3D DNR, HLC, BLC, OSD, Privacy mask, ROI, Corridor mod, EIS ( žiroskopska stabilizacija slike ), Umanjuje False Alarme, Metadata ( Boja automobila, da li je motocikl ili auto, kod ljudi godine, naočare da li nosi, pol osobe...)
- Zaštita:** IP66
- Napajanje i potrošnja:** AC 24V ±25%, DC 24V ±25%, PoE++ (IEEE 802.3bt) (IEEE802.3bt switch required), potrošnja od 16-51W
- Radna Temperatura:** -40°C ~ 70°C (-22°F ~ 140°F),
- Vlažnost:** ≤95% RH (ne kondenzujuće)
- Dimenzije (ΦxV):** 357× 106 × 194mm (14.1" × 4.2" × 7.7")
- Kompatibilni nosači i pribor:** TR-CE45-IN, TR-UF45-A-IN, TR-SE45-IN, TR-SE45-A-IN, TR-WE45-A- IN, TR-WE45-B-IN, TR-JB12-IN, TR-UP08-A-IN, TR-UC08-A-IN, TR-UP08-B-IN, TR-UC08-B-IN